



**polar** light  
a light that never ends

# LED Tube



## Specification LED Tube

High PF 0.92, high power efficiency: 93%, low THD 15%  
 No flickering, constant output current;  
 Aluminum heatsink inside to make good heat dissipation  
 Mitsubishi PC cover, it can keep the same cover for more than 8 years.  
 Lifespan: 50,000hrs.  
 5 years warranty  
 150-200lm/W

## Product data

Physical Characteristics		Photometric Characteristics	
Size	1198x28mm	Color Temperature	3500-6000K
LED	CREE	Beam Angle	305D
Socket Type	G13	Color Rendering Index	Ra80
Lampshade	milky	Lumen Output	150lm/w-190lm/w
Rated Lifetime	50000Hrs	Colour Consistency	<6
Nominal lifetime	50000Hrs		
		Environmental characteristics	
Electrical Characteristics		Energy rating	A
Lamp Wattage	6W-24W	Storage Humidity	<90%
Input Voltage	AC 86-305V		
Frequency	50/60Hz	Specification of the tube	
Power Factor	0.95	Length B	1198mm
Dimmable	No	Length A	1213mm
Starting Time	0.5(max)s	Length C	28mm
Energy saving product	Yes		

# LED Tube



Product	Wattages	Lumens	Voltages	Size	Lifetime	Warranty	Color Temperature	Certificate	LED	Photo
<b>T8 LED Tube_60</b>	5W - 10W	158 lm/W	86-305V	60cm	60 000h	5 years	3000K-6000K	CE/ENEC	CREE	
<b>T8 LED Tube_60</b>	6W- 12W	170 lm/W	86-305V	60cm	60 000h	5 years	3000K-6000K	CE/ENEC	CREE	
<b>T8 LED Tube_60</b>	7W- 12W	180 lm/W	86-305V	60cm	50 000h	5 years	3000K-6000K	CE/ENEC	CREE	
<b>T8 LED Tube_120</b>	10W- 20W	158 lm/W	86-305V	120cm	50 000h	5 years	3000K-6000K	CE/ENEC	CREE	
<b>T8 LED Tube_120</b>	12W- 24W	170 lm/W	86-305V	120cm	50 000h	5 years	3000K-6000K	CE/ENEC	CREE	
<b>T8 LED Tube_120</b>	15W- 24W	180 lm/W	86-305V	120cm	50 000h	5 years	3000K-6000K	CE/ENEC	CREE	
<b>T8 LED Tube_120</b>	20W- 24W	190 lm/W	86-305V	120cm	50 000h	5 years	3000K-6000K	CE/ENEC	CREE	

Certificate : CE,ENEC,ISO

a light that never ends



Veternik magj. Prishtinë-Ferizaj  
10000 Prishtinë, Kosovë  
+381 38 602 302  
info@bauenergy-rks.com  
www.bauenergy-rks.com